

CLASSIC AUTO SUPPLY CO., INC.

POSITION OF DECALS

- ◆ **Jacking instructions, 55** - centered on trunk divider board
 56/57 - center of trunk lid
- ◆ **Heater** - On heater plenum, top surface engine compartment. Reads when viewer is facing rear of car.
- ◆ **Tire pressure** - Glove box door
- ◆ **Air cleaner, 55/56** - on side of air cleaner base; LH (drivers) side start decal about 1" back from hood seal retainer
 57 - on flat surface of air cleaner top
- ◆ **Air scoop plate** - on scoop plate inside so it can be read when plate is installed
- ◆ **Folding top** - glove box door
- ◆ **Automatic transmission** - glove box door
- ◆ **Oil filter can** - (Used with non-spin on filters) Position midway on canister; decal goes around canister, not lengthwise
- ◆ **Data plate** - on data plate
- ◆ **Voltage regulator** - on top of voltage regulator cover
- ◆ **Coil** - on coil: decal wraps around coil close to the bottom (metal end); top of the decal is toward the top of the coil (wire end)
- ◆ **Starter** - on starter, lengthwise; so it could be seen easily if car had no heater
 55 uses metal plate attached with rivets
 56 & 57 use decal
- ◆ **Generator** - on generator, lengthwise and centered so it can be easily seen
 55 uses metal plate attached with rivets
 56 & 57 use decal
- ◆ **Door latch** - (56 only) one on each side, on *body* below striker plate with no LD1
 Late 56 use LD1 only on driver door with no door latch decal
- ◆ **Lifeguard** - Late 56 and 57 on drivers *door* below door latch star wheel

Self adhesive decals. Crack and peel off backing to expose adhesive surface. Apply carefully to clean surface. Repositioning is not possible.

Water transfer decals. These are preferred for these applications because the plastic film is much thinner. To apply soak the decal in room temperature water for 30-60 seconds or until the decal slides easily on the paper backing. Remove the decal from the backing by holding the decal in the desired position and carefully slide the backing out from beneath the decal. Use the edge of the backing to carefully squeegee away any air bubbles or excess water from beneath the decal. Allow to dry for 24 hours before cleaning off excess adhesive around the decal with a damp cloth.

If there are any further questions regarding placement or application of the decals, please feel free to call our tech help line at 740-622-9700.